



## BEHR® Interior/Exterior Bonding Primer Metal Primer

- Adheres to Tough-to-Paint Surfaces
- Reduces Need for Sanding Dense, Glossy Surfaces
- Improves Topcoat Adhesion
- Works Under Alkyd, Oil and

- Water-Based Topcoats
- Quick Recoat Time
- Tintable up to 2 oz. of Colorant per Gallon

No. 432 White



**30 Min** Dries to Touch  
**1 Hr** Ready to Topcoat



**300-400** Sq. Ft.  
Coverage per Gallon



**Soap & Water**  
Clean-Up



**Protect**  
from Freezing

### WHERE TO USE

Over properly prepared uncoated and previously painted interior or exterior surfaces. Ideal for Kynar®, PVC, vinyl, Formica®, glass, tile, glazed brick, fiberglass, chalky paints, glossy finishes, architectural plastics, and metals. If using as a primer for epoxies, lacquers, products containing xylene or other hot solvents, allow to dry for 24 hours before topcoating; test for compatibility in a discrete area first before full coat application. Not recommended for floors or horizontal surfaces subject to prolonged water contact.

### PREPARATION

All surfaces must be properly prepared and cleaned. While BEHR® Bonding Primer is formulated to adhere without sanding, it is recommended that a small area be tested for adhesion prior to beginning the job. Remove loose paint, wash off chalk, dirt and grease with detergent, rinse well and allow to dry. Remove mildew stains with a mildew stain removing product. Remove all dust with a damp cloth, allow to dry. Remove loose rust, peeling paint and mill scale with a scraper, wire brush or sandpaper. Clean bare metal surfaces in accordance with The Society for Protective Coatings (SSPC) specifications.

### APPLICATION

Apply when air and surface temperatures are between 50-90°F (10-32°C). Use a high quality 3/8-1/2" nap roller cover on smooth surfaces or 1/2-3/4" nap roller cover on semi-rough or porous surfaces, nylon/polyester brush or an airless sprayer (.015"-.021" spray tip, 60 mesh filter). Stir primer occasionally. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. Topcoat within 14 days. For dramatic color changes, tint primer with up to 2 fl oz of colorant per gallon.

### DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit [behr.com](http://behr.com) for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**\*LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. **To obtain warranty service, call 1-800-854-0133.** Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**⚠ WARNING** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. < 100 g/L • REV. 05/19