



**BEHR**  
PREMIUM

INTERIOR/EXTERIOR

# CABINET, DOOR & TRIM ENAMEL



## CABINET, DOOR & TRIM PAINT FOR A FLAWLESS FINISH

BEHR PREMIUM® Cabinet, Door & Trim Interior/Exterior Enamel offers excellent flow & leveling and dries to a hard, durable finish. The paint provides all-weather protection which is great for exterior projects. Its outstanding early block resistance allows for quick return to service, making it ideal for use on cabinets, doors, trim, molding, windows, shutters, and woodwork. Available in satin and semi-gloss finishes.



# OUTSTANDING EARLY BLOCK RESISTANCE



## CABINET, DOOR & TRIM ENAMEL KEY FEATURES AND BENEFITS

### Outstanding Early Block Resistance

Provides tack-free film that keeps painted surfaces from sticking together

### Fast Drying

Allows recoat in just 2 hours\*; reducing down time and allowing quick return to service

### Excellent Flow & Leveling

Provides a smooth finish

### Resists Dirt, Grime and Household Chemicals

Prolongs life of the finish

### All-Weather Protection

Helps to resist against weather elements

### Mildew-Resistant Paint Finish

Provides effective protection from mold and mildew on the dried paint film

### Low VOC (< 50 g/L excluding colorants)

Meets the most stringent VOC regulations nationwide

### Easy Soap and Water Clean-Up

No solvent disposal issues

### Tintable to a Full Range of Colors

Expands color options

\*Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.

## Ideal for use on cabinets, doors, trim, molding, windows and shutters.

Also suitable for use on properly prepared drywall, masonry, and metal surfaces.



DOOR: Jojoba N390-3




TRIM: Night Blooming Jasmine YL-W10



CABINET: Back to Nature S340-4

## COMPARATIVE TEST DATA



BEHR PREMIUM®  
Cabinet, Door & Trim Enamel  
Semi-Gloss



NATIONAL BRAND 1  
Semi-Gloss



NATIONAL BRAND 2  
Semi-Gloss

Paints tinted to a blue color are applied to sealed test charts at three mils wet film thickness. After drying for two hours, the charts are cut into two pieces, placed face-to-face, and then compressed with a weight that exerts a pressure of one pound-per-square inch. After 24 hours, the face-to-face sections are pulled apart with slow and steady force to evaluate how the paint resists sticking together.

The above test examples are photographs of the actual results. The actual results may be viewed by appointment at Behr Process Corporation.

## CONFORMANCE & COMPLIANCE (AS OF 05/2022)

SCAQMD	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC Phase II	YES	GREENGUARD®#	YES
OTC	YES	LEED® v.4†	YES

\*GREENGUARD is a registered trademark of UL Company.

†Please visit [www.usgbc.org/LEED](http://www.usgbc.org/LEED) for additional details.

## Your BEHR PRO® Rep/Your Painting Contractor



For more information on our products and services, visit [behrpro.com](http://behrpro.com).



©2022 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A.

COVER IMAGE/CABINET:  
WELDED IRON HDC-AC-17A

Exclusively at



SELL-SHEET-PRO-  
CABINET-AND-TRIM  
Item No. 50008676  
05/2022