

CABINET, DOOR & TRIM PAINT FOR A FLAWLESS FINISH

BEHR PREMIUM® Cabinet, Door & Trim Interior/Exterior Enamel offers excellent flow & leveling and dries to a hard, durable finish. The paint provides all-weather protection which is great for exterior projects. Its outstanding early block resistance allows for quick return to service, making it ideal for use on cabinets, doors, trim, molding, windows, shutters, and woodwork. Available in satin and semi-gloss finishes.

OUTSTANDING EARLY BLOCK RESISTANCE









CABINET, DOOR & TRIM ENAMEL KEY FEATURES AND BENEFITS



Outstanding Early Block Resistance

Provides tack-free film that keeps painted surfaces from sticking together

Fast Drying

Allows recoat in just 2 hours*; reducing down time and allowing quick return to service

Excellent Flow & Leveling Provides a smooth finish

Resists Dirt, Grime and **Household Chemicals** Prolongs life of the finish

All-Weather Protection

Helps to resist against weather elements

Mildew-Resistant **Paint Finish**

*Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.

Provides effective protection from mold and mildew on the dried paint film

Low VOC (< 50 g/L excluding colorants)

Meets the most stringent VOC regulations nationwide

Easy Soap and Water Clean-Up

No solvent disposal issues

Tintable to a Full Range of Colors

Expands color options

Ideal for use on cabinets, doors, trim, molding, windows and shutters. Also suitable for use on properly prepared drywall, masonry, and metal surfaces.

COMPARATIVE TEST DATA





NATIONAL BRAND 1 Semi-Gloss



NATIONAL BRAND 2 Semi-Gloss

Paints tinted to a blue color are applied to sealed test charts at three mils wet film thickness. After drying for two hours, the charts are cut into two pieces, placed face-to-face, and then compressed with a weight that exerts a pressure of one pound-per-square inch. After 24 hours, the face-to-face sections are pulled apart with slow and steady force to evaluate how the paint resists sticking together.

The above test examples are photographs of the actual results. The actual results may be viewed by appointment at Behr Process Corporation.

CONFORMANCE & COMPLIANCE (AS OF 05/2023)			
SCAQMD	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC Phase II	YES	GREENGUARD®#	YES
ОТС	YES	LEED® v.4 [†]	YES

*GREENGUARD is a registered trademark of UL Company.

'Please visit www.usgbc.org/LEED for additional details



COVER IMAGE/CABINET: WELDED IRON HDC-AC-17A



Exclusively at