



BEHR PREMIUM® Direct-To-Metal Semi-Gloss Paint (3200) Behr Paint Company

Final Assembly: Santa Ana, California, USA

Life Expectancy: Interior / Exterior: 7 / 10 Year(s)

Embodied Carbon: 1.44-1.64 kg CO₂eq ■

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Nepheline syenite; Clay; 1-(2-butoxy-1-methylethoxy)propan-2-ol; Aluminum Oxide; Polyurethane Resins; 2-Propenoic acid, homopolymer, ammonium salt; Alcohols, C9-11-branched and linear, butoxylated ethoxylated; Lubricating oils (petroleum), hydrotreated spent; Ammonium Hydroxide, NOS; Benzophenone; Nitrous acid, sodium salt; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Diuron; Zirconium oxide (ZrO₂); Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; 1,2-Benzisothiazol-3(2H)-one; Siloxanes and Silicones, di-Me, reaction products with silica; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Methyl methacrylate; n-Butyl acrylate; Propylene glycol

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0007

EXP. 01 APR 2026

Original Issue Date: 2025