



Behr® ECOMIX™ Interior Semi-Gloss (E3000) Behr Paint Company

Final Assembly: Santa Ana, California, USA; Heath, Ohio, USA

Life Expectancy: 15 Year(s)

Embodied Carbon: 1.04 kg CO₂eq ▲

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with ethyl 2-propenoate; Titanium dioxide; Nepheline syenite; Styrene methyl methacrylate copolymer; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Kaolin, calcined; Polyurethane Resins; Aluminum Oxide; attapulgite; 2-Propenoic acid, homopolymer, ammonium salt; Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-; Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; Alcohols, C12-14-secondary, ethoxylated; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; polysiloxane; Ammonium Hydroxide, NOS; Zirconium oxide (ZrO₂); Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, ammonium salt; Clay; **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**; Polyphosphoric acids, sodium salts; Sodium Hydroxide; Sulfuric acid, mono(2-ethylhexyl) ester, sodium salt; **1,2-Benzisothiazol-3(2H)-one**; Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Quartz; Magnesium oxide (MgO)

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: <5 g/L |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0038

EXP. 01 NOV 2026

Original Issue Date: 2025