



## BEHR PRO® Pre-Catalyzed Waterborne Epoxy Eggshell (HP140) Behr Paint Company

**Final Assembly:** Santa Ana, California, USA

**Life Expectancy:** Interior / Exterior: 7 / 10 Year(s)

**Embodied Carbon:** 0.262 kg CO<sub>2</sub>e ■

**Declared Unit:** 1 Square Meter

**End of Life Options:** Take Back Program (PaintCare), Recyclable (100%)

### Ingredients:

Water; Titanium dioxide; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Nepheline syenite; Aluminum Oxide; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Polyurethane Resins; attapulgite; Fatty acids, soya, epoxidized, Me esters; 2-Propenoic acid, homopolymer, sodium salt; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; polysiloxane; Zirconium oxide (ZrO<sub>2</sub>); Poly[oxy(methyl-1,2-ethanediyl)],  $\alpha$ -hydro- $\omega$ -hydroxy-; Diuron; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Clay; OS 2020; Sodium Hydroxide; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; **1,2-Benzisothiazol-3(2H)-one**; Quartz; Magnesium oxide (MgO); Carbamic acid, butyl-, 3-iodo-2-propynyl ester

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

BHR-0010  
EXP. 01 APR 2026  
Original Issue Date: 2025