



KILZ 3® PREMIUM Interior/Exterior Primer (1300) Behr Paint Company

Final Assembly: Multiple Locations in the USA

Life Expectancy: 10 Year(s)

Embodied Carbon: 1.26 kg CO₂eq ▲

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Nepheline syenite; Calcium Carbonate; Kaolin, calcined; Talc; Carbonic acid, magnesium salt (1:1); Polyurethane Resins; Aluminum Oxide; Hexanoic acid, 2-ethyl-, 1,2-ethanediybis(oxy-2,1-ethanediy) ester; **Distillates (petroleum), solvent-dewaxed heavy paraffinic**; 2-Propenoic acid, homopolymer, potassium salt; Soda Ash; Alcohols, C9-11, ethoxylated; Quartz; ACUSOL 820; Bentonite; Ammonia; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Amorphous silica; Nitrous acid, sodium salt; Calcium magnesium carbonate; **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**; Clay; Siloxanes and Silicones, di-Me, reaction products with silica; Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1); Zirconium oxide (ZrO₂); Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; 1,3-Propanediol, 2-bromo-2-nitro-; Chlorite-group minerals; Carbamic acid, butyl-, 3-iodo-2-propynyl ester

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <5 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0032
EXP. 01 NOV 2026
Original Issue Date: 2025