



## KILZ® PVA Interior Drywall Primer (PX010) Behr Paint Company

**Final Assembly:** Multiple Locations in the USA

**Life Expectancy:** 5 Year(s)

**Embodied Carbon:** 1.02 kg CO<sub>2</sub>eq ▲

**Declared Unit:** 1 Square Meter

**End of Life Options:** Take Back Program (PaintCare), Recyclable (100%)

### Ingredients:

Water; Calcium Carbonate; Kaolin, calcined; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Titanium dioxide; attapulgit; ACUSOL 820; Styrene methyl methacrylate copolymer; Nepheline syenite; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Quartz; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 2-hydroxyethyl 2-propenoate and 2-propenoic acid; Ammonium Hydroxide, NOS; Silica gel, pptd., cryst.-free; Silica, Amorphous; Aluminum Oxide; Nitrous acid, sodium salt; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Siloxanes and Silicones, di-Me, reaction products with silica; Magnesium oxide (MgO); 1,3-Propanediol, 2-bromo-2-nitro-; 2-Propenoic acid, homopolymer, potassium salt; Barium sulfate

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- LBC Red List Free      % Disclosed: 100% at 100ppm
- LBC Red List Approved      VOC Content: <50 g/L
- Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

BHR-0018

EXP. 01 MAY 2026

Original Issue Date: 2025