



BEHR PREMIUM PLUS® Exterior Flat (4050) Behr Paint Company

Final Assembly: Multiple Locations in USA

Life Expectancy: 20 Year(s)

Embodied Carbon: 0.803 kg CO₂eq ▲

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; Titanium dioxide; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Nepheline syenite; Styrene methyl methacrylate copolymer; Silica, Amorphous; Ethanol, 2-butoxy-, benzoate; Aluminum Oxide; Lubricating oils (petroleum), hydrotreated spent; 2-Propenoic acid, homopolymer, potassium salt; Zinc oxide; Polyurethane Resins; Alcohols, C9-11-branched and linear, butoxylated ethoxylated; attapulгите; Ammonium Hydroxide, NOS; Cellulose, 2-hydroxyethyl ether; Nitrous acid, sodium salt; Diuron; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Zirconium oxide (ZrO₂); Clay; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Phosphoric acid, mono-octyl ester, potassium salt (1:2); polysiloxane; Siloxanes and Silicones, di-Me, reaction products with silica; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; 3(2H)-Isothiazolone, 2-methyl-

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0020
EXP. 01 JUN 2026
Original Issue Date: 2025