



BEHR PREMIUM PLUS® Exterior Semi-Gloss Enamel (5050) Behr Paint Company

Final Assembly: Multiple Locations in the USA

Life Expectancy: 20 Year(s)

Embodied Carbon: 0.76 kg CO₂e ■

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Styrene methyl methacrylate copolymer; Ethanol, 2-butoxy-, benzoate; Polyurethane Resins; Aluminum Oxide; Nepheline syenite; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Zinc oxide; attapulgite; Ammonium Hydroxide, NOS; 2-Propenoic acid, homopolymer, ammonium salt; **Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Benzophenone;** Diuron; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Clay; Zirconium oxide (ZrO₂); **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester;** Sulfuric acid, mono(2-ethylhexyl) ester, sodium salt; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-; Quartz; **3(2H)-Isothiazolone, 2-methyl-**

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BHR-0028
EXP. 01 JUL 2026
Original Issue Date: 2025