



BEHR PREMIUM PLUS® Interior Satin Enamel (7050) Behr Paint Company

Final Assembly: Multiple Locations in USA

Life Expectancy: 15 Year(s)

Embodied Carbon: 0.27 kg CO₂eq

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Nepheline syenite; Styrene methyl methacrylate copolymer; Kaolin, calcined; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Polyurethane Resins; Aluminum hydroxide; Amorphous silica; attapulgit; Lubricating oils (petroleum), hydrotreated spent; 2-Propenoic acid, homopolymer, ammonium salt; Alcohols, C12-14-secondary, ethoxylated; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Sodium Hydroxide; Clay; Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-; polysiloxane; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-; **1,2-Benzisothiazol-3(2H)-one**; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Quartz; Siloxanes and Silicones, di-Me, reaction products with silica; **3(2H)-Isothiazolone, 2-methyl-**; Magnesium oxide (MgO); Sulfuric acid, mono(2-ethylhexyl) ester, sodium salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <5 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0013
EXP. 01 MAY 2026
Original Issue Date: 2025