

Declare.

BEHR PREMIUM PLUS® Interior/Exterior Hi-Gloss Enamel (8150) Behr Paint Company

Final Assembly: Multiple Locations in North America

Life Expectancy: 15 Year(s)

Embodied Carbon: 0.2775 kg CO₂eq

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Ethanol, 2-butoxy-, benzoate; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Aluminum hydroxide; Amorphous silica; Polyurethane Resins; Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Nitrous acid, sodium salt; 2-Propenoic acid, homopolymer, ammonium salt; 1-Propanol, 2-amino-2-methyl-; Paraffin; Ammonium Hydroxide, NOS; 1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]-; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Diuron; Clay; Alcohols, C16-18, ethoxylated; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; **3(2H)-Isothiazolone, 2-methyl-**; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Alcohols, C9-11, ethoxylated; **3(2H)-Isothiazolone, 5-chloro-2-methyl-**; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Methyl methacrylate; n-Butyl acrylate

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0012
EXP. 01 MAY 2026
Original Issue Date: 2025