

# Declare.

## BEHR PRO® Block Filler Primer (PR050) Behr Paint Company

**Final Assembly:** Santa Ana, California, USA

**Life Expectancy:** 10 Year(s)

**Embodied Carbon:** 3.04 kg CO<sub>2</sub>e ■

**Declared Unit:** 1 m<sup>2</sup> for 60 years

**End of Life Options:** Take Back Program (PaintCare), Recyclable (100%)

### Ingredients:

Calcium Carbonate; Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Talc; Titanium dioxide; Quartz; Wollastonite; Propylene glycol; Ethanol, 2-butoxy-, benzoate; attapulgit; OS 2020; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Ammonium Hydroxide, NOS; Cellulose, 2-hydroxyethyl ether; Alcohols, C12-14-secondary, ethoxylated; Aluminum hydroxide; Amorphous silica; **1,2-Benzisothiazol-3(2H)-one**; Calcium magnesium carbonate; Carbonic acid, magnesium salt (1:1); Chlorite-group minerals; Diopside (CaMg(SiO<sub>3</sub>)<sub>2</sub>); Poly(oxy-1,2-ethanediyl),  $\alpha$ -hydro- $\omega$ -hydroxy-; Siloxanes and Silicones, di-Me, reaction products with silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Magnesium oxide (MgO)

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <100 g/L
- Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

BHR-0011  
EXP. 01 APR 2026  
Original Issue Date: 2025