

Declare.

BEHR PRO® Concrete & Masonry Primer (PR060) Behr Paint Company

Final Assembly: Roanoke, Texas, USA

Life Expectancy: 10 Year(s)

Embodied Carbon: 1.03 kg CO₂eq 

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 2-hydroxyethyl 2-propenoate and 2-propenoic acid; Titanium dioxide; Kaolin, calcined; Nepheline syenite; Cetylhydroxyethylcellulose; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Aluminum Oxide; Ammonium Hydroxide, NOS; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, ammonium salt; Alcohols, C9-11-branched and linear, butoxylated ethoxylated; attapulgit; 2-Propenoic acid, homopolymer, ammonium salt; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Phosphoric acid, disodium salt; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Amorphous silica; Zirconium oxide (ZrO₂); 1,3-Propanediol, 2-bromo-2-nitro-; Quartz; Silica gel, pptd., cryst.-free

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <100 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0009

EXP. 01 APR 2026

Original Issue Date: 2025