

Declare.

BEHR PRO® i300 Interior Dead Flat (PR310) Behr Paint Company

Final Assembly: Multiple locations in the United States

Life Expectancy: 15 Year(s)

Embodied Carbon: 1.252 kg CO₂e 

Declared Unit: 1m² for 60 years

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; Titanium dioxide; poly(ethylene-vinyl acetate); Kaolin, calcined; Calcium Carbonate; Nepheline syenite; Wollastonite; Silica, Amorphous; Styrene methyl methacrylate copolymer; Aluminum Oxide; OS 2020; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Cetylhydroxyethylcellulose; Propanoic acid, 3-ethoxy-, ethyl ester; Mica-group minerals; attapulgite; Lubricating oils (petroleum), hydrotreated spent; Quartz; polysiloxane; Ammonium Hydroxide, NOS; Amorphous silica; Diopside (CaMg(SiO₃)₂); 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Zirconium oxide (ZrO₂); Clay; **1,2-Benzisothiazol-3(2H)-one**; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, methyloxirane and oxirane; Phosphoric acid, disodium salt; Siloxanes and Silicones, di-Me, reaction products with silica; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Feldspar; Magnesium oxide (MgO)

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: <5 g/L |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0001
EXP. 01 JAN 2026
Original Issue Date: 2024