



BEHR PRO® i300 Interior Eggshell (PR330) Behr Paint Company

Final Assembly: Multiple locations in the United States

Life Expectancy: 15 Year(s)

Embodied Carbon: 1.138 kg CO₂e ■

Declared Unit: 1m² for 60 years

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; Titanium dioxide; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Pumice; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Calcium Carbonate; Styrene methyl methacrylate copolymer; Propanoic acid, 3-ethoxy-, ethyl ester; Aluminum Oxide; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; attapulgite; Lubricating oils (petroleum), hydrotreated spent; Cetylhydroxyethylcellulose; Polyurethane Resins; OS 2020; Ammonium Hydroxide, NOS; Quartz; Amorphous silica; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Zirconium oxide (ZrO₂); Clay; **1,2-Benzisothiazol-3(2H)-one**; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, methyloxirane and oxirane; polysiloxane; Siloxanes and Silicones, di-Me, reaction products with silica; Zinc oxide; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Phosphoric acid, disodium salt; Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; Magnesium oxide (MgO)

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <5 g/L
- Declared

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BHR-0002
EXP. 01 JAN 2026
Original Issue Date: 2024