

Declare.

BEHR PRO® i300 Interior Semi-Gloss (PR370) Behr Paint Company

Final Assembly: Multiple locations in the United States

Life Expectancy: 15 Year(s)

Embodied Carbon: 1.118kg CO₂eq

Declared Unit: 1m² for 60 years

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; Titanium dioxide; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Propanoic acid, 3-ethoxy-, ethyl ester; Kaolin, calcined; Nepheline syenite; Styrene methyl methacrylate copolymer; Aluminum hydroxide; Amorphous silica; attapulgite; Polyurethane Resins; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; Lubricating oils (petroleum), hydrotreated spent; Cetylhydroxyethylcellulose; Ammonium Hydroxide, NOS; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; OS 2020; 1,2-Benzisothiazol-3(2H)-one; Clay; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; Quartz; polysiloxane; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Magnesium oxide (MgO); Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; Siloxanes and Silicones, di-Me, reaction products with silica; 3(2H)-Isothiazolone, 2-methyl-; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Phosphoric acid, disodium salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <5 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0003
EXP. 01 JAN 2026
Original Issue Date: 2024