



BEHR PRO® e600 Exterior Satin Paint (PR640) Behr Paint Company

Final Assembly: Multiple Locations in the USA

Life Expectancy: 20 Year(s)

Embodied Carbon: 0.725 kg CO₂eq ■

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Mica-group minerals; Styrene methyl methacrylate copolymer; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Nepheline syenite; Aluminum Oxide; Polyurethane Resins; 2-Propenoic acid, homopolymer, ammonium salt; Ammonium Hydroxide, NOS; Cellulose, 2-hydroxyethyl ether; attapulgite; Alcohols, C9-11-branched and linear, butoxylated ethoxylated; Diopside (CaMg(SiO₃)₂); Feldspar; Diuron; Amorphous silica; **Distillates (petroleum), solvent-dewaxed heavy paraffinic**; Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Phosphoric acid, monoethyl ester, potassium salt (1:2); Zirconium oxide (ZrO₂); **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**; Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1); Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; **1,2-Benzisothiazol-3(2H)-one**; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Quartz; **3(2H)-Isothiazolone, 2-methyl-**; Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester; Siloxanes and Silicones, di-Me, reaction products with silica

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: <50 g/L |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BHR-0035
EXP. 01 NOV 2026
Original Issue Date: 2025