

# Declare.

## BEHR PRO® e600 Exterior Semi-Gloss Paint (PR670) Behr Paint Company

**Final Assembly:** Multiple Locations in the USA

**Life Expectancy:** 20 Year(s)

**Embodied Carbon:** 0.741 kg CO<sub>2</sub>eq

**Declared Unit:** 1 Square Meter

**End of Life Options:** Take Back Program (PaintCare), Recyclable (100%)

### Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Styrene methyl methacrylate copolymer; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Nepheline syenite; Aluminum Oxide; Polyurethane Resins; attapulgit; Cetylhydroxyethylcellulose; Ammonium Hydroxide, NOS; 2-Propenoic acid, homopolymer, ammonium salt; Alcohols, C9-11-branched and linear, butoxylated ethoxylated; Siloxanes and Silicones, di-Me, 3-hydroxypropyl Me, ethoxylated propoxylated; Amorphous silica; Diuron; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Zirconium oxide (ZrO<sub>2</sub>); Phosphoric acid, monoocetyl ester, potassium salt (1:2); Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; polysiloxane; Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1); Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; 1,2-Benzisothiazol-3(2H)-one; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Phosphoric acid, disodium salt; Quartz; 3(2H)-isothiazolone, 2-methyl-; Magnesium oxide (MgO); Oxirane, methyl-, polymer with oxirane

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: <50 g/L
- Declared

**I-10 Interior Performance:** Not Applicable

**I-14 Responsible Sourcing:** Not Applicable

BHR-0036

EXP. 01 NOV 2026

Original Issue Date: 2025