



BEHR ULTRA® Exterior Flat (4850) Behr Paint Company

Final Assembly: Multiple Locations in the USA

Life Expectancy: 20 Year(s)

Embodied Carbon: 0.795 kg CO₂eq ■

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; Nepheline syenite; Titanium dioxide; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Styrene methyl methacrylate copolymer; Wollastonite; Ethanol, 2-butoxy-, benzoate; Aluminum Oxide; 2-Propenoic acid, homopolymer, ammonium salt; attapulgite; Polyurethane Resins; Zinc oxide; polysiloxane; **Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, ammonium salt; Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; Ammonium Hydroxide, NOS; Amorphous silica; Phosphoric acid, mono-octyl ester, potassium salt (1:2); 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; **Benzophenone**; Diuron; Quartz; Zirconium oxide (ZrO₂); Clay; Diopside (CaMg(SiO₃)₂); **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**; Calcium Carbonate; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-; **3(2H)-isothiazolone, 2-methyl-**; Alcohols, C9-11-iso-, C10-rich, ethoxylated, polymers with epichlorohydrin; Magnesium oxide (MgO)

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: <50 g/L |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BHR-0022
EXP. 01 JUN 2026
Original Issue Date: 2025