



BEHR PREMIUM® COLOR CHANGING MULTI-PURPOSE SPACKLING

BS00217 5.5 oz Tube
BS00408 16 oz Tub
BS00404 32 oz Tub

- Ideal for Small and Large Hole Repairs
- Excellent Adhesion
- Sag, Shrink, and Crack Resistant
- Patch & Primer**
- Interior/Exterior

**Prime for non-flat paints



Protect from Freezing



Goes on Pink, Dries White Paint Ready in 30 Minutes*



Easy Application

For Use On: Drywall, Plaster, Wood and Stucco



Soap & Water Clean-Up

*Repairs 1" wide and 1/8" depth or smaller may be painted in as little as 30 minutes depending on temperature, humidity, depth of fill

BEHR PREMIUM® Color Changing Multi-Purpose Spackling is a lightweight spackling compound ideal for filling in small and large holes or cracks. This ready to use mix applies pink and dries white, allowing you to know when it is time to sand or paint. It also has excellent adhesion properties that resists sagging, shrinking, and cracking for a durable, smooth surface.

PREPARATION

- The surface must be clean and dry before applying spackling compound.

APPLICATION

- Mix material gently before use.
- Spread with a putty knife and slightly overfill hole or crack.
- Allow to dry thoroughly before sanding or painting.
- Sand flush with surface.
- Repeat as necessary.
- Spackling compound will change color from pink to white when surface can accept a second application or is ready to be sanded and painted.
- Prime for topcoats of any sheen higher than flat to prevent flashing.

CLEAN-UP & DISPOSAL

Clean tools, equipment and excess uncured material with soap and water immediately after use. For disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

To retain the effectiveness of the color changing formula, use adamp cloth to wipe access material out of the container rim, close immediately after use.

- Store container in a cool, dry place away from extreme heat or cold. Protect from freezing.
- For best results, prime before painting with any sheen higher than flat to prevent flashing.
- Do not apply at temperatures below 50 °F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use as a caulk or sealant for structural joints, cracks, floors, or exterior substrates where expansion and contraction may occur.
- For exterior use, seal and topcoat with an exterior system.
- Wash hands thoroughly after handling.
- Shelf life of unopened container is 12 months from date of manufacture when stored under normal conditions.

Visit behr.com for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey.** To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

WARNING: This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING: IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: TITANIUM DIOXIDE, CALCIUM CARBONATE AND CRYSTALLINE SILICA. Avoid contact with skin and eyes. Do not breathe dusts, vapor, or spray mist. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.



©2024 Behr Process LLC
Santa Ana, CA 92705 U.S.A. • behr.com
REV. 12/24