



BEHR® WATER-BASED PRE STAIN WOOD CONDITIONER

No. B2080 Series

Clear

- Prepares Wood Surfaces for Water-Based Staining
- Helps Prevent Streaks & Blotches
- Use Prior to Staining
- Excellent Penetration
- Helps Promote Even Staining



Prep Before Use



1 Coat Application



Spread Rate:
100 Sq. Ft. / Qt.



Clean-Up:
Soap & Water

READY TO USE. PROTECT FROM FREEZING.

Prior to applying BEHR Water-Based Wood Stains. Not for use with oil-based stains. For oil-based stains, pretreat wood with BEHR Oil-Based Pre-Stain Wood Conditioner.

SURFACE PREPARATION†

(Proper surface preparation is required)

- Before applying BEHR Pre-Stain Wood Conditioner to bare or stripped wood surfaces, sand wood surfaces in the direction of grain to the desired smoothness. Remove all dust from the surface with a tack cloth.

APPLICATION (The following steps are recommended for best results.)

- Stir thoroughly before using. Do not shake or thin.
- Use a nylon or nylon/polyester brush or a saturated clean cloth and apply liberally to all areas of the wood surface including edges.
- Allow to penetrate between 5-10 minutes, and then wipe off any noticeable excess with a clean, dry cloth.
- Apply BEHR Water-Based Wood Stain or BEHR Water-Based Stain & Poly In One. Follow all label instructions.
- Allow Pre-Stain to dry for up to 20 minutes before applying Wood Stain.
- Sand lightly prior to staining to remove grain raise.

DRY TIME

- Dries in 20 minutes.

DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service

LIMITED WARRANTY

- Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

†**WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

 **WARNING** Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.



©2021 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 9/21