



## BEHR PREMIUM® Concrete & Masonry Protector & Waterproofer

No. 980 Natural

- Interior/Exterior
- Silicone Enhanced To Keep Water Out
- Penetrates The Surface Up To 1/2 Inch
- For Brick, Concrete, Stucco & Tile
- 10 Year Limited Guaranteed



**Spread Rate:**  
250 Sq. Ft.



**Dry Time:**  
24 - 48 Hr. to cure



**Clean-Up:**  
Soap & Water



**Protect**  
from Freezing

**CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

### WHERE TO USE

**Horizontal and Vertical uncoated Concrete and Masonry surfaces such as:** Concrete Block, Pavers, Stucco, Brick, Unglazed Tiles, Exposed Aggregate Concrete, Concrete, Porous Natural Stones Such As Sandstone . Not recommended for use on areas subject to hydrostatic pressure such as basement walls or floors.

### PREPARATION †

**(Proper surface preparation is required.)** All surfaces must be clean, sound, dry and free of any dirt, oil and grease. New concrete must cure for a minimum of 30 days. Use a paint stripper to remove any previous coatings or sealers. Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper. Test: Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.. Follow all label instructions.

### APPLICATION

**DO NOT THIN. Stir or shake before applying.** Use product when temperature is between 50 – 90° F (10 - 32° C). Apply until saturated by brush, roller or garden sprayer to a dry surface. Remove any puddles by spreading product to drier areas or by wiping up excess with a clean cloth. On vertical surfaces, apply from the bottom up and saturate well.

**LIMITED WARRANTY** Behr Process Corporation warrants to the original residential consumer purchaser the performance of this product as described on this label for 10 years on vertical and horizontal surfaces, from the date of purchase, for so long as you reside in your home. **THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS.** This warranty is not transferable. If this product is found not to perform as specified upon inspection by our representative during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

### DRY TIME

Once dried, rough, vertical surfaces may be coated with an oil or latex-based paint or primer. Follow all label instructions. "Do not paint dense concrete surfaces, such as horizontal concrete floors, after applying this product."

### DISPOSAL

Clean all equipment immediately with warm, soapy water. Properly dispose of all soiled rags and **protect unused product from freezing.** For disposal of empty containers and unused paint, contact your household refuse collection service.

**† WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2014 Behr Process Corporation  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <120 g/L (Low Solids) • REV. 3/16