

## Project Skill Level: Intermediate DIY'er

### For Best Results

To promote adhesion and durability of your topcoat, use a PREMIUM PLUS® primer. Not interested in applying a primer? Consider using PREMIUM PLUS ULTRA™ products—innovatively developed as a paint and primer in one.



### Step 1

Begin your painting project by pouring thoroughly mixed paint into a bucket and dipping a quality 2"–2½" wide nylon/polyester brush into the paint.

**TIP:** When working outside, it is best to work out of direct sunlight and when temperatures are 50°–90° F with moderate humidity.



### Step 2

With your brush, paint the shutter slats starting at the top of the shutter.

**TIP:** To eliminate unwanted brush strokes, take a lighter stroke over the newly painted area.



### Step 3

Beginning at a top corner of the shutter, paint the side edge of the shutter where it meets the body of the house.



### Step 4

Continue until all side edges around the shutter are complete. Wipe off the excess paint that has overlapped onto the stiles.



### Step 5

Return to the top of the shutter and begin painting the face of the shutter frame.





## Step 6

Continue until the shutter is complete.

**TIP:** For optimum results in quality of color and finish, apply a second coat.

Color Used: Autumn Leaves ECC-31-3

## Recommended BEHR Products


 PREMIUM PLUS ULTRA™ Exterior Paints

 PREMIUM PLUS® Exterior Primers

 PREMIUM PLUS® Exterior Paints

## Suggested Equipment

 Brush (2"–2½")

 Bucket

 Vinyl Gloves

 Ladder

 Paint Can Opener

 Protective Apparel

 Rags

 Stir Stick