



## BEHR PREMIUM® Gloss Enamel Porch & Patio Floor Paint

- Resists Scuffing, Fading, Cracking and Peeling
- Mildew Resistant Finish
- 100% Acrylic Latex
- High-Gloss Sheen

No. 6705-N Ultra Pure White®  
No. 6730 Deep Base  
No. 6795 Slate Gray



**Spread Rate:**  
Rough 200-300 Sq. Ft.  
Smooth 300-400 Sq. Ft.



**Dry Time:**  
1 Hr. Dry to Touch.  
4-6 Hr. Recoat



**Clean-Up:**  
Soap & Water



**Protect**  
from Freezing

**CAUTION:** Painted surfaces may become slippery when wet.  
Follow all label instructions.

### WHERE TO USE

On properly prepared, previously painted or primed Interior/Exterior surfaces. Ideal for Porches, Floors, Decks, Basement Floors, Patios, Siding, Trim, Furniture and Trellises. **Do not use on areas subject to automotive tires.**

### PREPARATION†

**(Proper surface preparation is required.)** All surfaces must be clean, sound, dry and free of any dirt, oil and grease. Remove mildew stains with a mildew stain removing product. **New or Weathered Wood:** Use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. Lightly sand to remove remaining wood fibers/fuzz. **Painted Surfaces-Wood:** For a painted surface in sound condition, use a product to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper to remove old coating. Scuff sand glossy surfaces. Use stainless steel or galvanized nails to prevent nail staining. Countersink nail heads, repair imperfections and sand smooth. Remove all dust with a damp cloth, allow to dry. **Uncoated Concrete or Masonry Surfaces:** Allow new surfaces to cure 30 days. Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper. **Painted Surfaces-Concrete:** For a painted surface in sound condition, use a product to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface. Scuff sand glossy surfaces. Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

### PRIME

**Interior Wood:** Use a product such as BEHR PREMIUM PLUS® No. 75 All-In-One Primer & Sealer. **Exterior Wood:** Use a product such as BEHR PREMIUM PLUS No. 436 Multi-Surface Primer & Sealer. **Interior/Exterior Concrete or Masonry:** Over uncoated surfaces, use a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer.

**LIMITED WARRANTY** Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

### APPLICATION

Use product when the surface and air temperatures are between 50 - 90° F (10 - 32° C). Stir paint occasionally. When working with more than one can of the same product, intermix to ensure color uniformity. Use a high quality 3/8" - 1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 - .021" spray tip, 60 mesh filter). Spread rate varies, depending on the surface texture, porosity and application method. Additional coats may be required for optimal hide and durability. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

### DRY TIME

Longer dry time required in cooler temperatures and in higher humidity. Allow 72 hours before subjecting to normal use. After 30 days, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

### DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

**† WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2015 Behr Process Corporation  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <100 g/L • REV. 04/16