



## BEHR PREMIUM PLUS WITH STYLE® Faux Glaze

No. 748 Faux Glaze

- Straight, Diagonal & Wavy Lines
- Patch Weaving • Fabric • Colorwashing
- Color Blending • Stippling & Speckling
- Smooth Leather • Soft Suede

### IMPORTANT: DO NOT OPEN CAN WITHOUT READING THESE INSTRUCTIONS. PROTECT FROM FREEZING.

This water-based translucent product is to be blended with BEHR PREMIUM PLUS® Interior paints or BEHR PREMIUM PLUS ULTRA® Interior Paint and Primer in One. The paint and glaze mixture extends the paint's open time to allow you to create unique decorative wall designs.

#### WHERE TO USE

- Properly painted Interior surfaces. Ideal for Family Rooms, Living Rooms, Dining Rooms, Bedrooms, Kids' Rooms, Hallways, Kitchens, Bathrooms, Doors, Trim and Ceilings.

#### PREPARATION†

- Remove loose paint, wash off any dirt and grease with detergent and remove mildew stains with a mildew stain removing product. Rinse and allow to dry. Scuff sand glossy surfaces.
- Countersink nailheads, repair imperfections and sand smooth. Remove all dust with a damp cloth and allow to dry. Allow new stucco, plaster and masonry to cure 30 days before priming. Use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75. Apply Interior Eggshell, Satin or Semi-Gloss sheen for the base color according to label instructions.

#### MIXING THE GLAZE COLOR

- In a plastic container, blend 1 part paint (1 quart) to 4 parts glaze (1 gallon) for each selected glaze color. Stir glaze mixture until thoroughly blended and occasionally during application.

#### APPLICATION

Refer to [behr.com](http://behr.com) for additional instructions on application. Dry time recommendations are based on 77°F (25°C) and 50% humidity and will vary depending on the air temperature/humidity and how thick the product is applied.

- Using the appropriate tool and technique, apply the glaze color over the dried base color.
- Work in 3 x 3' (90 x 90 cm) areas or smaller depending on the technique.
- Blend from section to section in a random pattern and maintain a wet edge to ensure smooth transitions.
- Typical coverage is 400 sq. ft (37 m<sup>2</sup>) per gallon. Coverage may vary depending upon the surface and the desired effect.

**LIMITED WARRANTY** Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2011 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <350 g/L • REV. 05/11

#### DRY TIME

- Dries to touch in 1 hour at 75°F (24°C) and 50% humidity.
- Allow 4 hours to dry between coats. Longer dry time required in cooler temperatures and in higher humidity.
- After 30 days, the surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

#### CLEAN-UP

- Wash tools with soap and water. Wipe excess product from lip of container prior to sealing to keep glaze from gluing lid closed. Dried spills must be cleaned with lacquer thinner or paint remover.
- Properly dispose of all soiled rags and **protect unused product from freezing**. For disposal of empty containers and unused paint, contact your household refuse collection service.

Refer to [behr.com](http://behr.com) for additional tips, expert project advice and perfect color coordination with ColorSmart by BEHR™

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**