



## BEHR Premium Plus with Style® Venetian Plaster Topcoat

No. 775 Clear Satin

- Use in High Moisture & High Traffic Areas
- Mildew Resistant Finish

**IMPORTANT: DO NOT OPEN CAN WITHOUT READING THESE INSTRUCTIONS. PROTECT FROM FREEZING.**

### WHERE TO USE

- As a clear protective topcoat to increase the durability of BEHR® VENETIAN PLASTER in high moisture and high traffic areas. Dries to a satin sheen.

### PREPARATION†

- Apply after BEHR® PREMIUM WITH STYLE VENETIAN PLASTER finish has completely dried, approximately 24 hours. VENETIAN PLASTER must be burnished prior to topcoat application.

### APPLICATION

Refer to [behr.com](http://behr.com) for additional instructions on application.

- DO NOT THIN. Stir occasionally. Use product when the surface and air temperatures are between 50-90°F (10-32°C).
- Apply using a straight-edged, flexible steel trowel or wall scraper. Hold trowel at an angle and spread a very thin, even coat of the product across the surface.
- Remove any excess topcoat with a damp rag or sponge. The topcoat will dry to a Satin sheen and darken the tone and/or color of the finish.
- Typical spread rate is 200 sq. ft. (19 m<sup>2</sup>) per quart.

### DRY TIME

- Dries in 24 hours at 75°F (24°C) and 50% humidity. Additional dry time is needed in cooler temperatures and higher humidity. After 2 weeks, the surface may be cleaned with a mild, non-abrasive liquid detergent.

### CLEAN-UP

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of empty containers and unused paint, contact your household refuse collection service.

Refer to [behr.com](http://behr.com) for additional tips, expert project advice and perfect color coordination with ColorSmart by BEHR™.

- † **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**LIMITED WARRANTY** Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2011 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <275 g/L • REV. 05/11

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**