



BEHR PREMIUM® Quick Dry Oil Base Wood Finish

- No. 4900 Clear
- No. 4901 Cedar Naturaltone
- No. 4902 Redwood
- No. 4929 Chocolate
- No. 4904 Cordovan Brown

- Dries in 60 Minutes
- Our Most Advanced Oil Formula
- Can Be Applied to Damp Wood
- For Decks, Fences & Siding
- Resists Rain after 60 Minutes
- Protects Against UV Damage



Must Prep
Before Applying
Wood Finish



1 Coat
Application



Spread Rate:
Covers up to 300 Sq. Ft.
per Gallon



Clean-Up
Mineral Spirits
or Paint Thinner

CAUTION: Finished surfaces may become slippery when wet.

WHERE TO USE

Recommended for properly prepared new to slightly weathered, unsealed exterior wood surfaces (0-5 years exposure) such as: Decks, Railings, Shakes, Shingles, Siding, Fences, and Wood Patio Furniture.

PREPARATION †

(Proper surface preparation is required.) For failing coatings or to remove loose wood fibers, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood. When No. 64 is not needed, a product such as No. 63 **MUST** be used to remove mill glaze and clean the wood surface. After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Remove any standing water and allow the area to dry to under 20% moisture content (approximately 1-3 hours of dry time under normal conditions) before coating. If any sanding is required to remove wood fibers/fuzz, allow the surface to dry completely. Protect all surrounding areas not intended to be stained including vegetation, windows, concrete, etc. See behr.com for additional product information.

APPLICATION

(For best results, a lambswool pad applicator is recommended over large deck areas.) Shake product thoroughly prior to opening. Must apply between 40-90°F (4.5-32°C). Avoid applying in direct sunlight or to hot surfaces. Coating will resist rain after approximately 1 hour. Product may be applied to damp wood surfaces (i.e. within 1-3 hours of rainfall, rinsing, and removal of any standing water).

Use caution when pouring product as some splashing may occur. Immediately clean up any inadvertent spills with mineral spirits or paint thinner. For multiple gallons, combine into larger container for color uniformity. Mix product occasionally throughout application. Test product for penetration and color on a small hidden area before proceeding. Use a natural bristle brush for areas requiring more accuracy.

Use of rollers is not recommended. A high quality pump sprayer with a variable tip may be used. Lightly saturate the surface and back-brush any excess finish. Be sure to eliminate puddling and evenly distribute the finish. Maintain a wet edge when applying. Apply product end-to-end or to board lengths to prevent lap marks. Avoid applying finish too heavily. One coat application. Applying a thin second coat will darken the color of the finish if desired. For optimum performance, coat all accessible sides especially board ends.

MAINTENANCE

When color has faded and water is readily absorbed by the substrate, prep/clean with a product such as BEHR PREMIUM No. 63, allow to dry, and apply a new/fresh coat of wood finish. Product can be applied annually if needed.

DRY TIME

Finish dries in 60 minutes (i.e. dry to touch, allows for foot traffic and placement of furniture).

DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <250 g/L • REV. 3/18

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying.

DANGER FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. VENTILATION REQUIRED. TO AVOID INHALATION AND COMBUSTION HAZARDS (SEE BELOW). DO NOT USE THIS PRODUCT UNLESS YOU CAN ACHIEVE CROSS-VENTILATION BY OPENING WINDOWS AND DOORS DURING APPLICATION AND DRYING. CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL. May affect the brain and nervous system causing dizziness, headache or nausea. Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Follow respirator manufacturer's directions for respirator use. Causes eye irritation and may cause an allergic skin reaction. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling and before smoking and eating. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **VAPORS MAY CAUSE FLASH FIRE.** Keep away from sparks, heat and open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. Close container after each use. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.