



## BEHR PREMIUM® Self-Priming 1 Part Epoxy Concrete & Garage

- Interior/Exterior Satin Finish
- Self-Priming, No-Mix Formula
- Available in Custom Colors
- Resists Hot Tire Pick-Up
- Stain, Chemical & Weather Resistant

No. 900 White Base  
No. 902 Slate Gray  
No. 930 Deep Base



**Spread Rate:**  
Rough 300-400 Sq. Ft.  
Smooth 400-500 Sq. Ft.



**Dry Time:**  
1 Hr. Dry to Touch.  
4-6 Hr. Recoat



**Clean-Up:**  
Soap & Water



**Protect**  
from Freezing

**CAUTION:** Painted surfaces may become slippery when wet. Adding a non-skid floor additive may help prevent slipping.

### WHERE TO USE

Interior/Exterior surfaces such as: Porous Concrete, Masonry, Stone and Brick. Ideal for horizontal surfaces such as: Garage Floors, Driveways, Basement Floors, Porches and Pool Decks. DO NOT use on vertical surfaces or areas subject to hydrostatic pressure. NOT for industrial use or areas subject to forklifts.

### PREPARATION † (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease.  
**New and Uncoated Concrete or Masonry Surfaces:**
- Allow new surfaces to cure 30 days.
- Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper.
- Wipe your fingers over the clean, dry floor to check for dust or powder. Ensure there is no residue on your fingers that may have been left from the etcher. If residue is found, rinse the surface to remove residue. Allow the surface to dry completely. Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.
- Apply a Primer Coat: Apply 1 coat of BEHR PREMIUM® Concrete & Garage Self-Priming 1-Part Epoxy, or a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface.  
**Painted, Stained or Sealed Concrete:**
- For a painted surface in sound condition, use a product to clean and prepare the surface.
- If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface.
- Scuff sand glossy surfaces.
- Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.
- Spot prime all bare concrete areas with BEHR PREMIUM Concrete & Garage Self-Priming 1-Part Epoxy or with a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface.

### APPLICATION

- DO NOT THIN.
- Intermix all cans of same product to ensure color uniformity.
- Stir before and occasionally during application. Use product when air and surface temperatures are between 50-90° F (10-32° C).
- Apply to dry concrete. Do not apply if rain or heavy dew is expected within 24 hours.
- Apply a thin, even coat using a 3/8" nap roller cover, nylon/polyester brush or an airless sprayer (.015"-.021" spray tip, 60 mesh filter).
- Allow first coat to dry before deciding if a second coat is necessary.
- For uniformity apply second coat in a criss-cross pattern.
- An annual touch-up may be required in areas subject to tire traffic.

### DRY TIME

- Longer dry time required in cooler temperatures and in higher humidity.
- The floor may be subjected to light foot traffic after 24 hours.
- Allow 72 hours before subjecting surface to heavy foot traffic or repositioning furniture.
- Allow 7 days before subjecting to automotive tires.
- Premature heavy traffic will cause paint failure requiring spot recoating.
- If necessary, corrugated cardboard may be used underneath automobile tires after 72 hours.
- Wait at least 30 days before rinsing or cleaning. Use a mild detergent as needed.
- Abrasive cleaners and pressure-washers should be used carefully to avoid premature paint failure.

### DISPOSAL

- Properly dispose of all soiled rags.
- To recycle or properly dispose of product in your community, contact your household refuse collection service.

### LIMITED WARRANTY

Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**† WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

**⚠ WARNING** Cancer and Reproductive Harm [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2018 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <50 g/L • REV. 03/18