

BEHR PREMIUM® Anti-Slip Floor Finish Additive

- Creates a slip resistant finish
- Suitable for use on concrete or wood surfaces
- Can be used on oil or latex paints, stains, & sealers
- Easy to clean

IMPORTANT! DO NOT OPEN POUCH WITHOUT READING INSTRUCTIONS.

BEHR PREMUM® ANTI-SLIP FLOOR FINISH ADDITIVE is a unique texture additive, which, when mixed with a finished product container of paint or solid color stain creates a slip-resistant coating for all types of interior and exterior floor surfaces. This product will not change the color of the floor coating. For a high-quality finish use one of the many BEHR PREMIUM floor coating products:

PORCH & PATIO FLOOR PAINT • 1-PART EPOXY • SOLID COLOR CONCRETE STAIN

APPLICATION:

Garage Floors • Patios • Stairs • Basements • Driveways • Walkways • Pool Decks

MIXING INSTRUCTIONS:

Add the proper amount of **BEHR PREMIUM ANTI-SLIP FLOOR FINISH ADDITIVE** directly to the container of any latex or oil-based floor coating finish and stir thoroughly until dispersed uniformly. Stir occasionally during application. Apply coating to floor surface using a brush or roller. Refer to all paint and stain manufacturer's product labels for specific instructions

FINISHED PRODUCT CONTAINER SIZE	1 QUART	1 GALLON	5 GALLONS
AMOUNT OF ADDITIVE NEEDED	1/4 POUCH	1 POUCH	5 POUCHES

on surface preparation and finish application. If applying more than one coat of floor finish, mix **ANTI-SLIP FLOOR FINISH ADDITIVE** only into the final top. Adding a anti-slip additive will reduce the lifespan of the product; therefore, retain any leftover paint for periodic maintenance re-coating.

This product, if added according to label directions, helps to prevent slipping by providing a slip-resistant coating. However, Behr does not warrant that this product will prevent accidents.

▲ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. CONTAINS: CARBON BLACK AND TITANIUM DIOXIDE. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF DUST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN — DO NOT TAKE INTERNALLY.

LIMITED WARRANTY Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product is found not to meet our manufacturing specifications upon inspection by our representative, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

