



# BEHR® FAST DRYING OIL-BASED POLYURETHANE

- Durable Clear Protective Finish
- Recoat in 2 Hours
- Resists Stains and Scratches
- Protects & Beautifies Interior Wood
- Dries to Touch in 2 Hours

No. B7110 Series

Available in  
Satin, Semi-Gloss,  
Gloss, and Matte



Prep Before Use



3 Coats Required



Spread Rate:  
15-20 Sq. Ft.



Clean-Up:  
Mineral Spirits

## WHERE TO USE

- Properly prepared interior unfinished and finished wood surfaces such as furniture, moldings, cabinets, trim and doors.

### SURFACE PREPARATION†

(The following steps are recommended for best results)

- For refinishing, remove all wax or cleaner build-up with wax stripper or degreaser, prior to sanding.
- Sand all surfaces in the direction of the wood grain to desired smoothness.
- Do not use steel wool.
- Remove all dust from sanded surfaces and clean with tack cloth.
- If desired, apply BEHR® Wood Stain. Follow all label instructions.

### APPLICATION

- Do not apply in direct sunlight or in temperatures below 55°F (10°C) and above 90°F (32°C).
- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use.
- Protect adjacent areas from overspray. Wet overspray can be removed with mineral spirits.
- Hold can vertically 12 inches from surface. Depress button fully and spray using an even, sweeping motion with slightly overlapping strokes. On unfinished wood, apply sufficient material to seal open joints, edges and end-grain.
- Apply thin coats to avoid runs and sags. Recoat within 2-4 hours. If unable to do so, wait a minimum of 72 hours, then lightly sand and recoat.
- Apply at least 3 coats on unfinished wood and 2 coats on surfaces already finished.
- After final coat, allow at least 24 hours before normal use.

Note: Above dry times are based on good ventilation, temperature of 77°F and 50% relative humidity. Lower temperature, higher humidity, lack of air movement or application of thick coats will extend drying times. Slight ambering may be experienced when Polyurethane is applied over light-colored wood surfaces. Always spot test on an inconspicuous area to ensure satisfactory results.

### NOZZLE CARE

- After each use, clear valve by holding can upside down and spraying until only clear gas comes out.
- If spray button becomes clogged, wear eye protection, wipe off button opening with lacquer thinner. Do not stick pin in spray button opening.

## LIMITED WARRANTY

- Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**†WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

**⚠ WARNING** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**IMPORTANT! STORAGE AND DISPOSAL: DANGER!** Rags, steel wool and waste soaked with BEHR FAST DRYING POLYURETHANE may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government control agency.

**VENTILATION REQUIRED:** To avoid inhalation and combustion hazards (see below), **DO NOT** use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **CONTAINS ACETONE, PROPANE, NAPHA, BUTANE AND PETROLEUM DISTILLATES. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE IRRITATION. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

**CAUTION: KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

DOT 2P M579

Max VOC: 67% by Weight - Max Product Weighted MIR: 0.85

**PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
REV. 8/18