



## BEHR® WATER-BASED SPAR URETHANE

No. B8200 Series  
Satin, Semi-Gloss, Gloss

- Durable Crystal Clear Protective Finish
- Fortified with UV Inhibitors
- For Exterior & Interior Wood Surfaces
- Dries to touch in 1 hour
- Water Resistant Finish
- Expands and Contracts with Temperature Change



Prep Before Use



3 Coats Required,  
4 Coats if Desired



Spread Rate:  
125 Sq. Ft. / Qt.



Clean-Up:  
Soap & Water

### READY TO USE. PROTECT FROM FREEZING.

**WHERE TO USE:** Properly prepared Interior/Exterior wood surfaces exposed to direct sunlight. Ideal for residential applications, patio furniture, doors and wood handrails. **NOT RECOMMENDED** for use on Exterior siding or Exterior wood decking and stairs. Do not use over painted surfaces, wax, shellac, fresh lacquer or lacquer sanding sealer.

**CAUTION:** Top coated surfaces may be slippery when wet.

### SURFACE PREPARATION†

(The following steps are recommended for best results.)

- For refinishing, remove all wax or cleaner build-up with a wax stripper or degreaser prior to sanding.
- Sand all surfaces in the direction of the wood grain to desired smoothness.
- DO NOT USE steel wool.
- Remove all dust from sanded surfaces and clean with tack cloth.

### APPLICATION

- Do not shake or thin. Do not apply in direct sunlight or in temperatures below 55°F (10°C) or above 90°F (32°C). Stir thoroughly prior to and during use.
- If wood stain color is desired, apply BEHR® Wood Stain. Follow all label instructions.
- Using a high quality nylon/polyester bristle brush, dip approximately an inch into the can, gently tapping it against the inside to remove any excess.
- Apply a thin, even coat following the direction of the grain. Make sure to maintain a wet edge.
- To minimize the brush marks and bubbles after staining, tip off the surface by holding the brush at a 45° angle and lightly run the bristles over the entire length of the wood.
- Do not puddle, over-brush or overlap finishes. Sand lightly between coats with fine sand paper. Remove all dust prior to applying additional coats.

### DRY TIME

- Dries to the touch in 1 hour. Sand or Recoat: 1 hour. After final coat, allow 12 - 24 hours before light use. Fully cured: 3 days after final coat.

### DISPOSAL

- For disposal of empty containers and unused product, contact your household refuse collection service.

### LIMITED WARRANTY

- Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**†WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.**

**⚠ WARNING** Cancer and Reproductive Harm –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**CAUTION IRRITANT MAY CAUSE AN ALLERGIC SKIN REACTION. CONTAINS: TRIETHYLAMINE, 2-BENZIMIDAZOLE CARBAMIC ACID, METHYL ETHER, AND DIURON. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS AND SPRAY MIST. WEAR EYE PROTECTION, GLOVES AND PROTECTIVE CLOTHING. USE WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; if on skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.**

**PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <275 g/L • REV. 7/19